

Standard Centre

Fixed Frame Scaribar

	Centre Frame	Standard Centre			
Narrow Centre	11' 10" (3.6m)				
Medium Centre	13' 0" (4.0m)				
Standard Centre	17' 9" (5.4m)	17' (5.2m)	19' (5.6m)	22' (6.7m)	24' (7.4m)

NUMBER OF TINES (set on 5 rows)

At 7" (180mm) spacings	29	31	37	41
At 8 ³ / ₄ " (225mm) spacings	23	25	29	33
At 10 ¹ / ₂ " (270mm) spacings	19	21	25	27

FRAME DIMENSIONS

Height (transport)	6' 10" (2.1m)	6' 10" (2.1m)	6' 10" (2.1m)	6' 10" (2.1m)
Width (transport)	17' 2" (5.3m)	18' 3" (5.6m)	22' 0" (6.7m)	24' 7" (7.5m)
Length	A Frame Length	16' 0"	16' 0"	16' 0"
	Main Frame Depth	11' 6"	11' 6"	11' 6"
	Total Length	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)

WEIGHT (at 7" tine spacing) kg

	3,700	3,800	4,300	4,500
--	-------	-------	-------	-------

TYRES

Centre Frame and Wings
Floating Hitch (Front)

← 15.5/80 x 24 →

KEY MEASUREMENTS

Under Frame Clearance
Under Tine Clearance
Road Transport Clearance
Working Depth

(common to all machines)

28"	(710mm)
23"	(575mm)
11 ¹ / ₄ "	(285mm)
6"	(150mm)

TINE BREAKOUT

	Low setting	Medium setting	High setting
Spring Tine – Light Spring	70lb (30kg)	105lb (47kg)	145lb (65kg)
	165lb (74kg)	260lb (116kg)	350lb (157kg)
	235lb (104kg)	365lb (163kg)	485lb (216kg)
Hydraulic Tine	75lb (35kg)	→ 660lb (300kg)	

