

Single Fold with Narrow Centre

		Single Fold with Narrow Centre					
Narrow Centre	Centre Frame	11' 10"	24'	27'	30'	31'	35'
		(3.6m)	(7.4m)	(8.1m)	(9.2m)	(9.5m)	(10.6m)
	Medium Centre	13' 0"					
		(4.0m)					
Standard Centre	17' 9"						
		(5.4m)					
NUMBER OF TINES (set on 5 rows)							
At 7"	(180mm) spacings	41	45	51	53	59	
At 8 ³ / ₄ "	(225mm) spacings	33	37	41	43	47	
At 10 ¹ / ₂ "	(270mm) spacings	26	30	34	36	38	
FRAME DIMENSIONS							
Height (transport)		10' 8"	12' 1"	13' 7"	14' 6"	15' 11"	
		(3.2m)	(3.7m)	(4.1m)	(4.4m)	(5.0m)	
Width (transport)		17' 7"	17' 7"	17' 7"	17' 7"	17' 7"	
		(5.4m)	(5.4m)	(5.4m)	(5.4m)	(5.4m)	
Length	A Frame Length	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"	
	Main Frame Depth	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	
	Total Length	27' 6"	27' 6"	27' 6"	27' 6"	27' 6"	
		(8.4m)	(8.4m)	(8.4m)	(8.4m)	(8.4m)	
WEIGHT (at 7" tine spacing) kg							
		5,100	5,500	5,800	5,900	6,400	
TYRES							
Centre Frame and Wings		← 15.5/80 x 24 →					
Floating Hitch (Front)							

KEY MEASUREMENTS

	(common to all machines)	
Under Frame Clearance	28"	(710mm)
Under Tine Clearance	23"	(575mm)
Road Transport Clearance	11 ¹ / ₄ "	(285mm)
Working Depth	6"	(150mm)

TINE BREAKOUT

	Low setting	Medium setting	High setting
Spring Tine – Light Spring	70lb	105lb	145lb
	(30kg)	(47kg)	(65kg)
Standard Spring	165lb	260lb	350lb
	(74kg)	(116kg)	(157kg)
Dual Spring	235lb	365lb	485lb
	(104kg)	(163kg)	(216kg)
Hydraulic Tine	75lb	→ 660lb	
	(35kg)	(300kg)	

Folded Wing Scaribar

