

Single Fold with Medium Centre

Folded Wing Scaribar

	Centre Frame	Single Fold with Medium Centre						
Narrow Centre	11'10" (3.6m)	*	*					
Medium Centre	13' 0" (4.0m)	30' (9.0m)	34' (10.3m)	35' (10.6m)	36' (11.0m)	38' (11.7m)	40' (12.1m)	41' (12.4m)
Standard Centre	17' 9" (5.4m)							
NUMBER OF TINES (set on 5 rows)								
At 7" (180mm) spacings		51	57	59	61	65	67	69
At 8 ³ / ₄ " (225mm) spacings		41	45	47	49	51	53	55
At 10 ¹ / ₂ " (270mm) spacings		34	38	38	40	42	44	46
FRAME DIMENSIONS								
Height (transport)		13' (3.9m)	14' 3" (4.5m)	15' 4" (4.7m)	16' (4.9m)	17' (5.2m)	17' 8" (5.4m)	18' 3" (5.6m)
Width (transport)		18' 11" (5.8m)	18' 11" (5.8m)	18' 11" (5.8m)	18' 11" (5.8m)	18' 11" (5.8m)	18' 11" (5.8m)	18' 11" (5.8m)
Length	A Frame Length	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"	16' 0"
	Main Frame Depth	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"	11' 6"
	Total Length	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)	27' 6" (8.4m)
WEIGHT (at 7" tine spacing) kg								
		6,000	6,300	6,400	6,400	6,600	6,700	6,900
TYRES								
Centre Frame and Wings		15.5/80 x 24						
Floating Hitch (Front)		10.5/80x18 (4 off)	10.5/80x18 (4 off)					



KEY MEASUREMENTS			
Under Frame Clearance	28"	(710mm)	
Under Tine Clearance	23"	(575mm)	
Road Transport Clearance	11 ¹ / ₄ "	(285mm)	
Working Depth	6"	(150mm)	
TINE BREAKOUT			
Spring Tine – Light Spring	70lb (30kg)	105lb (47kg)	145lb (65kg)
	165lb (74kg)	260lb (116kg)	350lb (157kg)
	235lb (104kg)	365lb (163kg)	485lb (216kg)
Dual Spring	75lb (35kg)	660lb (300kg)	

* Floating Hitch option available
 ** Floating Hitch model only